



QUICK CONNECT HOOK™

**WORKING LOAD LIMIT: UP TO 13,200 LBS.
WEB SLING EYE WIDTHS UP TO 3"**

Ideal for use with synthetic slings, CM Quick Connect Hooks are the quickest and easiest way to add hooks to any synthetic sling by eliminating the need for additional hardware or assembly tools. Designed with a large bearing surface, these hooks prevent the sling from bunching, allowing the sling to be used at full capacity. And, for easy selection, Quick Connect Hooks are color coded to match common industry synthetic sling capacities.

BENEFITS & FEATURES

QUICK & EFFICIENT ATTACHMENT

Hook design allows for quick and efficient rigging without the need for additional tools or hardware. Simply open the latch, slide in the sling, close the latch and put the sling into position – it's that easy.

LONGER SLING LIFE

Smooth, flat bearing surface prevents abrasive synthetic sling damage. Hook design also protects the sling, eliminating wear caused by sharp load edges and the need for additional edge protection.

LOW SLING WEIGHT AND COST

By eliminating the need for additional hardware or oversized components to prevent bunching, the weight savings synthetic slings provide will be maintained. Quick Connect Hooks allow for quick sling-to-load connection without relying on a choker or basket hitch, thus eliminating the need for longer, more expensive slings.

EASY SELECTION

Hooks are color coded to match common synthetic sling capacities. Working load limits are also forged into the hook for easy reference. (NOTE: Always refer to the synthetic sling tag and Quick Connect Hook for working load limit of the assembly.)

SECURE SLING ATTACHMENT

Hook eye is designed with a recessed area to ensure the sling stays in place. Sling will not come out of the eye unless purposely removed.

STRONG & DURABLE

Forged for optimum strength and durability. Each hook is individually proof tested to 2x the working load limit.

STANDARD HOOK LATCHES

Uses same latches as standard CM Clevlok® sling hooks.

I-BEAM DESIGN REDUCES OVERALL SLING WEIGHT

EMBOSSED FOR WORLDWIDE USE



WLL: 2,600 LBS.

COLOR CODED TO MATCH COMMON SYNTHETIC SLING CAPACITIES



WLL: 5,300 LBS.



WLL: 8,400 LBS.



WLL: 13,200 LBS.



SPECIFICATIONS

Color	Working Load Limit (lbs.)	Product Code	Latch Kit	Dimensions (in.)										Weight (lbs.)
				A	B	C	D	E	F	G	H	I	J	
Purple	2,600	M85030	4X85030	0.770	3.530	0.794	2.884	1.500	1.500	0.418	0.938	0.813	0.580	1.450
Green	5,300	M85060	4X85060	1.034	4.589	1.040	3.751	1.625	1.875	0.553	1.200	1.188	0.865	3.735
Yellow	8,400	M85090	4X435329	1.208	5.410	1.172	4.325	1.875	2.375	0.640	1.500	1.250	1.043	5.835
Red	13,200	M85120	4X455329	1.384	6.141	1.392	5.026	2.125	2.625	0.744	1.750	1.438	1.200	8.282

